

# What's in the Box?

| PART NO.     | QTY | DESCRIPTION           |
|--------------|-----|-----------------------|
| VS2P         | 1   | WUXGA 2-Port Splitter |
| Power Supply | 1   | PS5VDC2A              |
| User Manual  | 1   |                       |

# Technical Specifications

| VIDEO             |   |
|-------------------|---|
| Format            | VGA RGB Analog (75Ω, 0.7Vp-p)                 |
| Resolution        | Up to 1600x1200 @ 85Hz/2048x1536 @ 60Hz       |
| Input Interface   | (1) HD-15 Male                                |
| Output Interface  | (2) HD-15 Female                              |
| H Frequency Range | 30-95KHz                                      |
| V Frequency Range | 50-180Hz                                      |
| OTHER             |   |
| DDC Signal        | 5 Volts [peak-to-peak], TTL                   |
| TDMS Signal       | 1.2 Volts[peak-to-peak], TTL                  |
| Power             | External 5VDC2A                               |
| Dimensions        | 5.325"W x 1"H x 3"D                           |
| Weight            | 0.25 lbs.                                     |
| Approvals         | Device: CE, ROHS<br>Power Supply: C-UL US, CE |

© Copyright 2017 Smart-AVI, All Rights Reserved

## NOTICE

The information contained in this document is subject to change without notice. Smart-AVI makes no warranty of any kind with regard to this material, including but not limited to, implied warranties of merchantability and fitness for any particular purpose.

Smart-AVI will not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance or use of this material.

No part of this document may be photocopied, reproduced or translated into another language without prior written consent from Smart-AVI.

For more information, visit [www.smartavi.com](http://www.smartavi.com).

**Smart-AVI**  
SMART AUDIO VIDEO INNOVATION

## Installation Manual

### VS2P 2-Port Video WUXGA Splitter



Connect One VGA Output Signal to Two Displays

## Rack Mountable Option



Our SmartRack is the perfect solution to allow virtually all SmartAVI devices to be custom mounted in a standard 19" server rack. The SmartRack is fully adjustable and can secure/organize several devices.

**Smart-AVI**  
SMART AUDIO VIDEO INNOVATION

SmartAVI, Inc. / Twitter: smartavi  
11651 Vanowen St. North Hollywood, CA 91605  
Tel: (818) 503-6200 Fax: (818) 503-6208  
<http://www.SmartAVI.com>

[www.smartavi.com](http://www.smartavi.com)

## Introduction

The VS2P is a 2-port WUXGA splitter that allows a computer to display one VGA video signal on two monitors simultaneously.


## Features

- Split WUXGA signal into two outputs
- Resolutions up to 1600x1200 @ 85Hz and up to 2048x1536 @ 60Hz
- Easy installation
- 300 MHz Bandwidth
- Compact metal enclosure

## Applications

- Home Theater Integration
- Restaurants and Bars
- Digital Signage Deployment
- Information Kiosks/Displays
- Film/Recording Studios

## Product - Installation Diagram



## Installation

1. Turn off the computer and the displays.
2. Connect an VGA cable from the computer to the input port on the VS2P.
3. Connect the displays to the VGA outputs on the VS2P.
4. Connect the power cord to the VS2P.
5. Power on the computer and the displays.

