

DP | DVI-I | HDMI VIDEO WALL CONTROLLER WITH 4K INPUT AND 1080P OUTPUT ON UP TO FOUR HDMI SCREENS

FEATURES

- INPUT: (1) DP, (1) DVI-I, (1) HDMI 4K Input
- OUTPUT: (4) 1080p HDMI, (1) HDMI Local Loop
- Input up to 4K (3840x2160 @ 30Hz)
- Output up to 1080p (1920x1080 @ 60Hz)
- Creative configuration modes, including:
 Full Video Wall | PIP | POP | Flip
- Supports VGA & Y/Pb/Pr when paired with a DVI-I adaptor
- Includes IR remote control & receiver.
- Control over web console or Android apps
- Plug-and-play for immediate use.


APPLICATIONS

- Airports
- Retail Stores
- Malls
- Movie Theaters
- Event Halls
- Hotel Lobbies
- Corporate Lobbies
- Sports Arenas
- Schools
- and more!

OVERVIEW

The XTREEM-WALL is a multi-format video wall controller with DisplayPort, DVI-I, and HDMI connectors. It is capable of input video resolutions up to 4K (3840x2160 @ 30Hz) and output resolutions up to 1080p (1920x1080 @ 60Hz) Full HD. One of SmartAVI's easiest and most effective solutions for building creatively configured video walls, the XTREEM-WALL is highly compatible with the most popular displays on the market and features a variety of stunning video wall modes.

APPLICATION DIAGRAM



FRONT AND BACK



XTREEM-WALL Back

AVAILABLE CONFIGURATIONS

The XTREEM-WALL features an engaging collection of display configurations that make crafting your ideal video wall easy, be it simple or XTREEM!



FULL VIDEO WALL MODE

Project video from a single input source across every screen on your video wall for an absorbing & largescale HD display.




PIP MODE

Place an window from any video source over a portion of your video wall for a Picture-inPicture (PIP) display.



POP MODE

Place video sources sideby-side in full screen or preserved aspect ratios: great for dividing up your video wall display.



FLIP MODE

Flip video sources from one half of the wall to the other to create a gorgeous and artistic reflected display.

HOW TO USE XTREEM-WALL

Using XTREEM-WALL is extremely simple and flexible enough to fit your unique control style. To take command of the controller, you can use:

FRONT PANEL BUTTONS

XTREEM-WALL features a simple push-button control panel for switching between sources and accessing preset configurations.

WEB CONTROL

Control everything from source resolution and aspect ratios to creative display modes from anywhere in the world over the Internet with SmartAVI's easy-to-use web control interface for the XTREEM-WALL.



IR CONTROL

Control source switching, resolution, creative display modes, and more at a convenient distance from the unit with our included RC-100 infrared remote control.

XTREEM-WALL APP

Maintain easy access to the XTREEM-WALL from an Android phone or tablet with SmartAVI's XTREEM-WALL apps.

Configure and control video walls on the fly without the hassle of having to log in and out of a browser-based web console. It's easy, it's effective, and FREE!



TECHNICAL SPECIFICATIONS

VIDEO & AUDIO		
Video Format	DP, DVI-I, HDMI	
Video Input	(1) DP; (1) DVI-I; (1) HDMI; *VGA & Y/Pb/Pr support with DVI-I adaptor	
Video Output	(4) HDMI; (1) HDMI Loopback	
Input Resolution	Up to 4K (3840 x 2160 @ 30 Hz)	
Output Resolution	Up to 1080p (1920 x 1080 @ 60 Hz)	
Audio Input/Output	HDMI Digital Audio	
Compliance	HDCP Compliant	

CONTROL	
Front Panel	Front-panel tactile switch buttons
IR Remote Control	RMT-XW Infrared Remote Control with IR-EYE3 receiver
Network	Web Control

OTHER		
Power	100-240VAC, PS12VDC 3.33A	
Max. Consumption	20 W	
Dimensions	17"W X 10.8"D X 1.9"H	
Weight	6.95 lbs	
Storage Temperature	-4 to 149 °F (-20 to 65 °C)	
Operating Temperature	32 to 122°F (0 to 50 °C)	
Humidity	Up to 85% (no condensation)	

PART NO.	DESCRIPTION
XTRW-S	4K IN-HD OUT HDMI/DP/DVI-I Video Wall Controller. Includes: [XTRW, IR-EYE3, RMT-XW (PS12VDC3.33A)]



